4,800 CFM Auto-Cleaning NeedlepointBipolar Ionization System

## **Product Description**

The GPS-FC48-AC is an auto-cleaning, needlepoint bipolar ionization system designed to handle up to 4,800 CFM. The unit is designed for multiple mounting options including fan inlet, interior duct wall or interior duct floor.

#### Standard Features

Universal voltage input, in-line On/Off switch, programmable autocleaning cycle, operation status LED, integral Building Automation System (BAS) alarm contacts, magnets for ease of installation and replaceable carbon fiber brush emitters.\*

\*Life cycle testing shows no mechanical degradation of the carbon fiber brushes due to repeated cleaning cycles

# Specifications

Input Voltage	24VAC to 240VAC
Amps	0.41A to 0.041A
Power	10 Watts
Frequency	50/60HZ
Total Ion Output	> 400 Million ions/cc/sec
Airflow Capacity	0 to 4,800 CFM or up to 12 tons
Temperature/Humidity	-20°F to 200°F / 0-100% RH
Unit Dimensions/Weight	11.1"L x 1.84"W x 3.52"H / 1.32 lbs
Electrical Listings	UL, cUL
Alarm Contact Rating	250VAC/ 1A, N.O. "dry" contact
Compliance & Certifications	UL 867, OSHPD Seismic (OSP), IAQP, CE

### Benefits









reduction

reduction

odors

savings

- · Particle Reduction and Smoke Control
- Odors Neutralized by destroying VOCs
- Pathogens Killed (Bacteria, Viruses, Mold), Helps to Control Allergens/ Asthma\*, Prevents Dirty Sock Syndrome
- Energy Savings of 30% by Reducing Outdoor Air Intake, reduces pressure loss by keeping coils clean without expensive UV system, and requires No Maintenance!

# Commercial Applications

- Animal Care
- Arenas and Stadiums
- · Child Care
- Food Service
- Healthcare
- Hospitality
- Institutional

- Manufacturing
- Office Buildings
- · Schools and Universities
- Theatre
- Transportation Hubs
- · Senior Care
- Worship



<sup>\*</sup> These statements are based on numerous customer testimonials and have not been evaluated by the FDA